


CU-TECH ThermexWELD exothermic welding aluminium conductors



stranded

sq mm		
25	W-A25	-
35	W-A50	-
50	W-A50	-
70	W-A50	-
95	W-A100	-
120	W-A100	-
150	W-A100	-
185	W-A150	-
240	W-A200	-
300	W-A250	-

STANDARD						
A-SS1-M-G6	M	-	T-110	T-110 / T-332		
A-SS1-M-H7	M	-	T-110	T-110 / T-332		
A-SS1-M-C9	M	-	T-110	T-110 / T-332		
A-SS1-M-C11	M	-	T-110	T-110 / T-332		
A-SS1-L-A13	L	-	T-110	T-110 / T-333		
A-SS1-L-C14	L	-	T-110	T-110 / T-333		
A-SS1-L-C16	L	-	T-111	T-111 / T-333		
A-SS1-L-C18	L	-	T-111	T-111 / T-333		
A-SS1-XL-A21	XL	-	T-111	T-111 / T-333		
A-SS1-XL-A23	XL	-	T-111	T-111 / T-333		

PIXY				



solid

dia mm		
8	W-A50	-
10	W-A100	-

STANDARD						
A-SS1-M-C8	M	-	T-110	T-110 / T-332		
A-SS1-M-C10	M	-	T-110	T-110 / T-332		

PIXY				