



CU-TECH ThermexWELD exothermic welding



stranded

sq mm		
10	W-Cu45	-
16	W-Cu45	-
16	W-Cu45	A-SCuK7
25	W-Cu45	-
30	W-Cu45	-
35	W-Cu45	-
50	W-Cu65	-
70	W-Cu115	-
95	W-Cu150	-
120	W-Cu115	-
150	W-Cu200	-
185	W-Cu250	-
240	2 x W-Cu150	-
300	2 x W-Cu200	-

STANDARD				
SP6-M-D4	M	T-431	T-231/T-281	T-110 / T-330
SP6-M-D5	M	T-431	T-231/T-281	T-110 / T-330
SP6-M-K7	M	T-431	T-231/T-281	T-110 / T-330
SP6-M-G6	M	T-431	T-231/T-281	T-110 / T-330
SP6-M-C7	M	T-431	T-231/T-281	T-110 / T-330
SP6-M-H7	M	T-431	T-231/T-281	T-110 / T-330
SP6-M-C9	M	T-431	T-231/T-281	T-110 / T-330
SP6-M-C11	M	T-431	T-231/T-281	T-110 / T-332
SP6-M-A13	M	T-431	T-231/T-281	T-110 / T-333
SP6-M-C14	M	T-431	T-231/T-281	T-110 / T-332
SP6-M-C16	M	T-431	T-231/T-281	T-110 / T-333
SP6-M-C18	M	T-431	T-231/T-281	T-110 / T-333
SP6-L-A21	L	T-431	T-111&T-281	T-111 / T-334
SP6-L-A23	L	T-431	T-111&T-281	T-111 / T-334

PIXY				
SP6-P-D4	P	T-400	T-231	T-107 / T-330
SP6-P-D5	P	T-400	T-231	T-107 / T-330
SP6-P-K7	P	T-400	T-231	T-107 / T-330
SP6-P-G6	P	T-400	T-231	T-107 / T-330
SP6-P-C7	P	T-400	T-231	T-107 / T-330
SP6-P-H7	P	T-400	T-231	T-107 / T-330
SP6-P-C9	P	T-400	T-231	T-107 / T-330
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-



solid

dia mm		
8	W-Cu65	-
10	W-Cu115	-
12	W-Cu115	-
16	W-Cu250	-

STANDARD				
SP6-M-C8	M	T-431	T-231/T-281	T-110 / T-330
SP6-M-C10	M	T-431	T-231/T-281	T-110 / T-332
SP6-M-C12	M	T-431	T-231/T-281	T-110 / T-332
SP6-M-C16	M	T-431	T-231/T-281	T-110 / T-333

PIXY				
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-