



CU-TECH ThermexWELD exothermic welding



stranded

sq mm		
10	W-Cu32	-
16	W-Cu25	-
16	W-Cu32	A-SCuK7
25	W-Cu32	-
30	W-Cu32	-
35	W-Cu32	-
50	W-Cu45	-
70	W-Cu65	-
95	W-Cu90	-
120	W-Cu115	-
150	W-Cu115	-
185	W-Cu150	-
240	W-Cu200	-
300	2 x W-Cu150	-

STANDARD				
SS1-M-D4	M	T-431	-	T-110 / T-330
SS1-M-D5	M	T-431	-	T-110 / T-330
SS1-M-K7	M	T-431	-	T-110 / T-330
SS1-M-G6	M	T-431	-	T-110 / T-330
SS1-M-C7	M	T-431	-	T-110 / T-330
SS1-M-H7	M	T-431	-	T-110 / T-330
SS1-M-C9	M	T-431	-	T-110 / T-330
SS1-M-C11	M	T-431	-	T-110 / T-330
SS1-M-A13	M	T-431	-	T-110 / T-332
SS1-M-C14	M	T-431	-	T-110 / T-332
SS1-M-C16	M	T-431	-	T-110 / T-333
SS1-M-C18	M	T-431	-	T-110 / T-333
SS1-L-A21	L	T-431	T-111	T-111 / T-333
SS1-L-A23	L	T-431	T-111	T-111 / T-333

PIXY				
SS1-P-D4	P	T-400	-	T-107 / T-330
SS1-P-D5	P	T-400	-	T-107 / T-330
SS1-P-K7	P	T-400	-	T-107 / T-330
SS1-P-G6	P	T-400	-	T-107 / T-330
SS1-P-C7	P	T-400	-	T-107 / T-330
SS1-P-H7	P	T-400	-	T-107 / T-330
SS1-P-C9	P	T-400	-	T-107 / T-330
SS1-P-C11	P	T-400	-	T-107 / T-330
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-
-	-	-	-	-



solid

dia mm		
8	W-Cu45	-
10	W-Cu65	-
12	W-Cu65	-
16	W-Cu115	-

SS1-M-C8	M	T-431	-	T-110 / T-330
SS1-M-C10	M	T-431	-	T-110 / T-330
SS1-M-C12	M	T-431	-	T-110 / T-330
SS1-M-C16	M	T-431	-	T-110 / T-332

SS1-M-C8	P	T-400	-	T-107 / T-330
SS1-M-C10	P	T-400	-	T-107 / T-330
-	-	-	-	-
-	-	-	-	-