


# CU-TECH ThermexWELD exothermic welding



stranded

sq mm		
10	W-Cu25	A-SCuD4
16	W-Cu15	-
16	W-Cu32	A-SCuK7
25	W-Cu25	-
30	W-Cu32	-
35	W-Cu32	-
50	W-Cu45	-
70	W-Cu65	-

STANDARD				
ST1-S-D4:xxx	S	T-410	-	T-109 / T-330
ST1-S-D5:xxx	S	T-410	-	T-109 / T-330
ST1-S-K7:xxx	S	T-410	-	T-109 / T-330
ST1-S-G6:xxx	S	T-410	-	T-109 / T-330
ST1-S-C7:xxx	S	T-410	-	T-109 / T-330
ST1-S-H7:xxx	S	T-410	-	T-109 / T-330
ST1-S-C9:xxx	S	T-410	-	T-109 / T-330
ST1-S-C11:xxx	S	T-410	-	T-109 / T-330

PIXY				

PIPE DIAMETER

	mm
A	60-70
B	70-90
C	90-105
D	105-115
E	115-125
F	125-135
G	135-145
H	145-165
J	165-190
K	190-220
L	220-250
M	250-300
N	300-330
P	330-350
R	350-450
S	450-550
T	550-700
U	700-1000
V	1000+